



Inlet connector

Actual size!



Native coupler compatibility



Ball-lock compatibility with an adapter

**Compact and precise, the GOVREG™ Secondary Regulator brings innovation to a product previously adapted and unchanged from the welding industry usage over 60 years ago!**

- Adapted from medical-grade technology
- Made from durable stainless steel
- Accepts a wide range of variable input pressures
- Outputs consistent and precise pressure and flow
- Simple and easy to maintain design
- Discreet and tamper-proof
- 3 variations and multiple inlet connectors to fit your application

**SPECIFICATIONS:**



**GOVREG B (Beer):**

- 0-4.1 bar output pressure
- G 1/4" Input
- Outlet with nuts passage at least 16.5 mm
- Adapter for inlet with nozzles AD 4.5 and AD 7.2 mm and thread AG 1/2"-16 UNS (CC)

**GOVREG S (Soda):**

- 2.7-7.2 bar output pressure
- G 1/4" Input
- Outlet with nuts passage at least 16.5 mm
- Adapter for inlet with nozzles AD 4.5 and AD 7.2 mm and thread AG 1/2"-16 UNS (CC)

**GOVREG High-flow:**

- 1.4-4.1 bar output pressure
- G 1/4" Input
- Outlet nut G 5/8" Female



Kits include the pressure adjustment tool for installers



Adjuster Adapter Ring

Adjuster tool



Eingangsadapter

Originalgröße!



Kompatibel mit Standardzapfköpfen



Mittels Adapter kompatibel mit Schnellkupplungen



Die Starterkits beinhalten das Druckeinstellwerkzeug für Installateure.



Eingangsadapterring



Einstellwerkzeug

**Der kompakte und präzise Sekundärregler GOVREG™ bringt Innovation für ein Produkt, welches seit dem Einsatz vor über 60 Jahren in der Schweißindustrie unverändert geblieben ist!**

- Angepasst von medizinischer Spitzentechnologie
- Hergestellt aus langlebigem Edelstahl
- Ein breites Spektrum an unterschiedlichen Eingangsdrücken kann verarbeitet werden
- Konstante und präzise Druck- und Durchflusswerte
- Einfaches und wartungsfreundliches Design
- Unauffällig und manipulationssicher
- 3 Varianten und mehrere Eingangsadapter entsprechend Ihrer Anforderungen

**CHARAKTERISTIKEN:**



**GOVREG B (Bier):**

- 0-4,1 bar Ausgangsdruck
- G 1/4" Eingangsgewinde
- Abgang mit Muttern, Durchgang mind. 16,5 mm
- Adapter für Eingang mit Tüllen AD 4,5 und AD 7,2 mm und Gewinde AG 1/2"-16 UNS (CC)



**GOVREG S (Soda):**

- 2,7-7,2 bar Ausgangsdruck
- G 1/4" Eingangsgewinde
- Abgang mit Muttern, Durchgang mind. 16,5 mm
- Adapter für Eingang mit Tüllen AD 4,5 und AD 7,2 mm und Gewinde AG 1/2"-16 UNS (CC)



**GOVREG High-flow:**

- 1,4-4,1 bar Ausgangsdruck
- G 1/4" Eingangsgewinde
- Abgang mit G 5/8" Mutter